



MAGNUM Industrial EP Gear Oils

PRODUCT # 192, 194

CAM2 MAGNUM Industrial EP Gear Oils are premium quality, extreme pressure gear oils for use in industrial service. These lubricants have good oxidation and thermal stability, have excellent demulsibility, are nonfoaming, and are noncorrosive to gear and bearing materials, provide excellent rust protection, and resist oil thickening and deterioration for long service life.

CAM2 MAGNUM Industrial EP Gear Oils are designed for use in conditions of high temperature and extreme pressure including enclosed gear systems, such as spur, bevel, herringbone, worm, and hypoid gears, chain drives, sprockets, slide guides and ways, and bearing sets. Misting oils and rock drill oils are other applications for these products. These fluids satisfy the requirements of U.S. Steel 224, AGMA 250.04, AGMA 251.02, and API GL-1 through GL-5 specifications.

TYPICAL PROPERTIES

| Product Code | 192 | 194 |
|-------------------------|-------|-------|
| ISO Grade | 220 | 460 |
| AGMA Number | 5EP | 7EP |
| Viscosity @ 40°C, cSt | 218 | 456 |
| Viscosity @ 100°C, cSt | 19 | 30.7 |
| Viscosity Index | 98 | 98 |
| Flash Point, °C | 440 | 450 |
| Pour Point, °C | 0 | 15 |
| Specific Gravity @ 60°F | 0.898 | 0.904 |
| Timken | 65 | 65 |
| Copper Corrosion | 1b | 1b |

