

# **CAM2<sup>®</sup> MAGNUM<sup>®</sup>**

## **PRODUCT BULLETIN**

### **MAGNUM TURBO D**

*API CH-4/SG*

**CAM2 MAGNUM Turbo D** heavy duty engine oils are premium quality, synthetic blend heavy-duty engine oils. **CAM2 Magnum Turbo D** heavy duty engine oils are formulated from premium base stocks and advanced additive technology, providing the highest levels of equipment protection available. **CAM2 Magnum Turbo D** heavy duty engine oils are suitable for use where an API CH4 is required. Equipment manufacturer's recommendations and conventional guides to lubricant selection should be followed to determine the best CAM2 Turbo D Motor Oil for a specific application.

## **FEATURES**

**CAM2 MAGNUM Turbo D Motor Oils provide:**

- Excellent protection from deposits
- Excellent bearing corrosion protection
- Excellent anti-wear properties
- Excellent anti-foam properties
- Excellent anti-rust properties
- Excellent soot control

## **APPLICATIONS**

**CAM2 MAGNUM Turbo D Motor Oils may be recommended for the following uses (see applications chart on page 2):**

- When CH-4, CG-4, CF-4, CF, CF-2 oils are required
- When SG, SF, SE, SD, SC oils are required





# **CAM2<sup>®</sup> MAGNUM<sup>®</sup>**

## **PRODUCT BULLETIN**

### **MAGNUM TURBO D**

*API CH-4/SG*

#### **TECHNICAL DATA**

SAE GRADE	15W-40	20W-50	25W-50	25W-60
Product Code	316	964	968	122
Density	7.24	7.28	7.34	7.46
Flash Point °C	220	220	220	220
Viscosity @ 40°C, cSt	116	177	173	208
Viscosity @ 100°C, cSt	15.5	20.5	20.31	22.5
Viscosity Index	135	135	132	132
API Licensed Service:	CH-4, CG-4, CF-4, CF-2, CE, SG			

**Contact your CAM2 representative or CAM2 distributor for additional information.**

***CAM2 INTERNATIONAL, LLC***

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 800-338-2262  
[www.CAM2.com](http://www.CAM2.com)