

PRODUCT BULLETIN

All Season Hydraulic Oil 5W-20

PRODUCT #148

CAM2 ALL SEASON HYDRAULIC OIL 5W-20 is a very high viscosity index hydraulic oil for use in mobile and industrial equipment operated in equipment that must be started at temperatures as low as -29°F and will continue to provide protection at temperatures as high as 194°F. This product meets SAE 5W-20 and ISO 46 viscosity grades. ALL SEASONS formulation offers superior shear stability performance.

CAM2 ALL SEASON AW HYDRAULIC OIL 5W-20 contains a polymeric viscosity improver and pour point depressant providing low temperature characteristics that may eliminate the need to change hydraulic oil seasonally. It is specially formulated for use in mobile equipment hydraulic circuits where wide temperature ranges are encountered. (Cherry pickers, bucket trucks and marine hydraulics).

It also can be used for traditional in-plant hydraulic applications, and exceeds most industry hydraulic fluid specifications, including: Denison HF-2, HF-0 Commercial Shearing, Vickers, Sunstrand, Rexnord, Cincinnati Milacron.

APPLICATIONS

May be recommended in the following equipment:

Eaton	Bosch Rexroth
Vickers	Oilgear
Denison	Hydreco
Komatsu	Dynex
Sauer-Danfoss	

SPECIFICATIONS

Eaton E-FDGN-TB002-E
Denison HF-0
ISO 11158 HV
DIN 51524 Part 3 HVLP
ASTM D6158 HV
AIST 127 & 127

FEATURES

- **Excellent thermal stability** - contain the latest thermally stable zinc type additives, virtually eliminating the formation of heat-related sludging in electro-hydraulic servos associated with conventional zinc-type oils.
- **Enhances, long lasting anti-wear protection** – specially developed additives form a protective layer on the wear surfaces, reducing component wear in high-pressure piston, vane, and gear hydraulic pumps.
- **Holds water in dispersion** – contains emulsifiers specifically designed to disperse water. CAM2 does not recommend oils that “separate,” “shed,” or “release” water. Separated water drawn through the hydraulic system can damage pumps and other components. If this water freezes, it can cause serious damage.
- **Low temperature performance** – allows start-ups down to -29°F; eliminates the need for seasonal fluid changes
- **Improved corrosion protection** – protects metal surfaces from rust



CAM2 INTERNATIONAL, LLC

211 Violet Street Suite 100 • Golden, CO 80401

Telephone 800/338-2262 • Fax: 303/679-8988

www.CAM2.com

PRODUCT BULLETIN

All Season Hydraulic Oil 5W-20

PRODUCT #148

TECHNICAL DATA

Product Code	148
ISO Viscosity Grade	46
Viscosity @ 40°C, cSt	41.05
Viscosity @ 100°C, cSt	7.68
Viscosity Index	159
Flash Point: °F	390
Pour Point: °F	-45
Oxidation Test Hours to 2.0 acid number	5000+
Low Temperature Pumpability	Pass
Dielectric, min. KV	+35
Rust Test	Pass

Contact your CAM2 representative or CAM2 distributor for additional information.

CAM2 INTERNATIONAL, LLC

211 Violet Street Suite 100 • Golden, CO 80401

Telephone 800/338-2262 • Fax: 303/679-8988

www.CAM2.com