

PRODUCT BULLETIN

Blue Blood Elite Euro 5W-30 Full Synthetic Motor Oil

API SL/CF

PRODUCT #299

CAM2 Blue Blood Euro motor oil is a Normal-SAPS, premium quality, full synthetic engine oil formulated from selected superior synthetic base oils and advanced high performance engine oil additive technology that makes it suitable for use in both gasoline and light-duty diesel automobiles.

CAM2 Blue Blood Euro 5W-40 meets European classification: ACEA A3/B4-16. BMW Longlife-01, MB P229.3/229.5, Porsche A40, VW 502.00/505.01, RN 0700/0710, PSA B71 2296, JASO MA2, API SN/CF and is suitable for use in Ford WSS-M2C913-C.

CAM2 Blue Blood Euro is the engine oil of choice for passenger cars, light trucks, powerboats, motorcycles and other stationary and mobile equipment when engine life and performance are important. Always consult your owner's manual.

FEATURES

- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures
- Excellent anti-wear, anti-foaming, anti-rust and corrosion protection.
- Excellent cold cranking capabilities
- Sustains maximum performance for longer, even when under pressure
- Maximizes short and long term engine performance
- Reduces engine deposits to help maximize engine response

APPLICATIONS

CAM2 Blue Blood Euro may be recommended for the following uses:

- In gasoline engines and turbo-charged engines
- Many engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- High Performance Engines
- Normal to frequently severe operating conditions
- Turbo-Chargers and Direct Injection engines

SPECIFICATIONS/APPROVALS

- When API SL, or SJ oils are required
- When API CF oils are required
- JASO MA2 (T903-2011)
- Porsche A40
- Mercedes Benz 229.31, 229.51
- Volkswagen 502 00/505 00
- Opel GM-LL-A/B-025
- Renault 0700, 0710
- MS-10725, MS-10850, MS-12991
- Fiat 9.55535.72*

See Technical Data on pg 2.



PRODUCT BULLETIN

Blue Blood Euro Full Synthetic Motor Oil API SL/CF

PRODUCT #299

TECHNICAL DATA

SAE GRADE	5W-30
Product Code	299
Viscosity @ 40°C, cSt	58.7
Viscosity @ 100°C, cSt	10.4
Viscosity Index	168
Ccs @ -30°C	5800
NOACK	<13.0
Color ASTM	3.0 max
Sulphated Ash, % m/m	1.2%

Contact your CAM2 representative or CAM2 distributor for additional information.