



## PRODUCT BULLETIN

# Blue Blood 2-Cycle TC-W3 Marine Oil Full Synthetic

Product # 324

**CAM2 Blue Blood Outboard 2-Cycle Marine Oil** is a premium quality, high performance formulation of 100% synthetic base oils and a sophisticated additive package that meets or exceeds the performance, protection and service requirements for ashless, high flash 2 cycle engine oil for use in modern, high performance water cooled and air cooled two stroke cycle engines.

### FEATURES

- Ashless additive system designed for today's 2 cycle engines
- Protects against ring sticking and cylinder wall scuffing
- High flash solvent means easy mixing with gasoline and
- Greater margin of safety in storage and handling.
- Protects against rust, wear, corrosion, and exhaust port plugging
- Reduces spark plug fouling and surface ignition
- Can be used at any fuel-to-oil ratio specified by OEM

**CAM2 Blue Blood Outboard 2-Cycle Marine Oil** is manufactured to our AQA™ standards of quality control that exceed industry standards. Every batch is laboratory tested from base stocks and additives to finished product, in order to consistently deliver an exceptional level of product quality.

### APPLICATIONS

Blue Blood Outboard 2-Cycle Marine Oil is designed for use in:

- Meets requirements of National Marine Manufacturers Association (NMMA) TC-W3, TC-W II, TC-W
- Suitable for applications calling for API Service Category TC
- Use in 2 cycle: outboard engines, snowmobiles, motorcycles, all-terrain vehicles, lawn mowers, golf carts, chain saws, and other two stroke cycle engines
- Where ashless oils are recommended.
- NOT suitable for 4 stroke cycle engines
- Misapplication may cause severe performance problems

### TYPICAL CHARACTERISTICS

Properties	Test Method ASTM D-	Typical Results
API Gravity	1298	33.1
Appearance	Visual	Blue
flash Point, COC °f/ °C	92	95/203
Pour Point, °f/ °C	97	-22/-30
Viscosity cSt @ 40°C	445	39.6
cSt @ 100°C		7.1
VI	2270	142
Brookfield Viscosity cP@ -40°C	2983	<7500

The above characteristics are typical of current production. While production will conform to CAM2's specification, slight variations may occur and do not affect performance.

**TC-W3™ Reg #: RL-14116U**

#### Special handling, notices or warnings

High pressure aerosol handle with care  
Use in well ventilated area  
Avoid contact with eyes  
Avoid prolonged or repeated contact with skin  
DO NOT INDUCE VOMITING

For more information, contact your CAM2 Representative or visit our website @ [www.CAM2.com](http://www.CAM2.com)

CAM2 INTERNATIONAL, LLC

211 Violet Street Suite 100 • Golden, CO 80401 Telephone 800/338-2262 • Fax: 303/679-8988  
[www.CAM2.com](http://www.CAM2.com)