



PRODUCT BULLETIN

CAM2 Blue Blood Elite HD Synthetic Engine Oil 15W-40

API CJ-4/SN

PRODUCT #392

CAM2 BLUE BLOOD ELITE HD SYNTHETIC MOTOR OIL with Engine DETOX, Fast Action Additives is the premium choice for preventative maintenance in vehicles that operate under severe driving and temperature conditions. CAM2 Blue Blood ELITE HD Synthetic Engine Oil 15W-40 provides superior wear protection, thermal and shear stability, and oxidative resistance. It meets or exceeds API service category CJ-4/SN, CI-4 Plus.

CAM2 BLUE BLOOD ELITE HD SYNTHETIC ENGINE OIL 15W-40 is suitable for use in Detroit Diesel®, Cummins®, Mack®, Caterpillar® and Volvo®. It is suitable for most naturally aspirated or turbo-charged diesel engines as well as exhaust gas re-circulated engines used in truck or off-highway equipment.

FEATURES

CAM2 Blue Blood ELITE HD Synthetic Engine Oil 15W-40 provides:

- Excellent protection from deposits at all operating temperatures.
- Excellent anti-wear, anti-foaming, anti-rust protection
- Excellent corrosion protection (EGR critical)
- Excellent soot control
- Extended drain capable

APPLICATIONS

CAM2 Blue Blood ELITE HD Synthetic Engine Oil 15W-40 may be recommended for the following uses:

- When CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4, CF. CF-2 oils are required
- When SN, SM, SL, SJ, SH, SG, SF oils are required
- All Heavy Duty Diesel Engines and EGR Designed Engines
- MACK EO-O Premium Plus
- Volvo VDS-4
- ACEA E9-08
- Cummins CES 20081
- DC 228.31



Applications continued on pg 2.

CAM2 INTERNATIONAL, LLC

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 800-338-2262

www.CAM2.com



PRODUCT BULLETIN

CAM2 Blue Blood Elite HD Synthetic Engine Oil 15W-40

API CJ-4/SN

PRODUCT #392

APPLICATIONS (continued)

- Detroit Fluids Specification DDC 93K218
- Renault VI RLD-3
- Caterpillar (ECF-3)
- MB 228.31

TYPICAL PROPERTIES

SAE GRADE	15W-40
Product Code	392
API	CJ-4/SN, CI-4 Plus
API Gravity	30
Viscosity @100°C, cSt	15.5
Sulfated Ash, wt.%	1
Total Base Number	10
Borderline Pumping, °C	-20
Pour Point:°C	-35
Flash Point:°C	240

Always consult owners manual for proper viscosity and performance recommendations

Contact your CAM2 representative or CAM2 distributor for additional information.

CAM2 INTERNATIONAL, LLC

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 800-338-2262

www.CAM2.com