

CAM2 ® Magnum® Gear Oils

CAM2® MAGNUM®GEAR OILS are manufactured from high quality base stocks. These oils are fortified with defoamers and rust and oxidation inhibitors for lasting trouble-free and sludge-free performance. MAGNUM®Gear Oils meet API GL-1 as well as AGMA R & O service classifications where low to moderate loading at moderate to high temperatures are encountered.

| | SAE 90 | SAE 140 |
|-------------|---------------------|---------------------|
| 12/1 QUART | 12903- 51005 | 12903- 51105 |
| 35 lb PAIL | 12903- 51012 | 12903- 51112 |
| 400 lb DRUM | 12903- 51055 | 12903- 51155 |



BULK

CAM2 ® Industrial EP Gear Oil

CAM2® Industrial EP Gear Oils are premium quality, extreme pressure gear oils for use in industrial service. These lubricants have good oxidation and thermal stability, are noncorrosive to gear and bearing materials, provide excellent rust protection, and resist oil thickening and deterioration for long service life. Excellent demulsibility and non-foaming.

| | EP 3 | 32 | EP 46 | EP 68 |
|-------------|---------------------|--------------------|-----------------------------|------------------------------|
| 400 lb DRUM | 1 80565-5 | 3455 809 | 65- 52455 | 80565- 51555 |
| TOTE | 80565-5 | 3400 809 | 65- 52400 | 80565- 51500 |
| BULK | 80565-5 | 3411 805 | 65- 52411 | 80565- 51511 |
| | | | | |
| | EP 10 | 00 | EP 150 | EP 220 |
| 400 lb DRUM | l 80565- 5 1 | 655 805 | 65- 51755 | 80565- 51855 |
| TOTE | 80565- 5 1 | 600 805 | 65- 51700 | 80565- 51800 |
| BULK | 80565- 5 1 | i 611 805 | 65- 51711 | 80565- 51811 |
| | | | | |
| | EP 320 | EP 460 | EP 680 | EP 1000 |
| 400 lb DRUM | 80565- 51955 | 80565- 5205 | 5 80565- 5215 | 5 80565- 52255 |
| TOTE | 80565- 51900 | 80565- 5200 | 0 80565- 5210 | 0 80565- 52200 |
| | | | | |

80565-**51911** 80565-**52011** 80565-**52111** 80565-**52211**

For more information about pricing and additional product items, please contact your CAM2 Sales Representative.

Visit Our Website! www.CAM2.com



Visit Our Facebook!





Manufactured & Distributed by CAM2® International, LLC 685 Haining Road, Vicksburg, MS 39183 USA Comments/Questions 800-338-2262



www.CAM2.com





CAM2 ® SYNAVEXTM Full Synthetic **Gear Oil LS**

GL-5

CANO SYNAVEX

API GL-5


875W-140 LS

ted Stip Gear Oil 35 POUNDS

CAM2[®] SYNAVEX™ FULL SYNTHETIC GEAR OILS (LS) are full synthetic heavy duty extreme pressure multi-grade gear oils manufactured with the highest quality synthetic base oil. Premium quality CAM2® SYNAVEX™ Gear Lubricants (LS), through the combination of naturally high viscosity index (low pour) synthetic base oils and advanced additive technology, are more economical than oils of lesser quality and lower initial cost. Using CAM2® SYNAVEX™ Gear Lubricants (LS) may allow longer drain intervals, extended equipment life. and a significant reduction in maintenance cost and downtime.

| | 75W-90 | 75W-140 | 80VV-140 |
|----------------|---------------------|---------------------|---------------------|
| 12/1 QUART | 80565- 50112 | 80565- 54712 | 80565- 50212 |
| 35 lb PAIL | 80565- 50105 | 80565- 54705 | 80565- 50205 |
| 42 lb RACKPACK | 80565- 50124 | 80565- 54724 | 80565- 50224 |
| 120 lb KEG | 80565- 50116 | 80565- 54716 | 80565- 50216 |
| 400 lb DRUM | 80565- 50155 | 80565- 54755 | 80565- 50255 |
| TOTE | 80565- 50100 | 80565- 54700 | 80565- 50200 |
| BULK | 80565- 50111 | 80565- 54711 | 80565- 50211 |

CAM2[®] High Performance EP Gear Oil



| | 80W-90 | 85W-140 |
|-------------|---------------------|---------------------|
| 12/1 QUART | 80565- 50712 | 80565- 50812 |
| 3/1 GAL | 80565- 50731 | 80565- 50831 |
| 35 lb PAIL | 80565- 50705 | 80565- 50805 |
| 120 lb KEG | 80565- 50716 | 80565- 50816 |
| 400 lb DRUM | 80565- 50755 | 80565- 50855 |
| TOTE | 80565- 50700 | 80565- 50800 |
| BULK | 80565- 50711 | 80565- 50811 |



CAM2 ® 80W-90 Gear Oil (LS)

CAM2® GEAR OIL 80W-90 LS are premium quality Limited Slip gear oils blended from highly refined high viscosity Index base stocks. These products meet the GL-5 requirements plus are formulated with Limited Slip functional additives.

| 35 lb PAIL | 80565- 51205 |
|-------------|---------------------|
| 120 lb KEG | 80565- 51216 |
| 400 lb DRUM | 80565- 51255 |
| TOTE | 80565- 51200 |
| BULK | 80565- 51211 |

CAM2 ® Magnum® Full Synthetic Gear Oil

CAM2® MAGNUM FULL SYNTHETIC GEAR OILS (LS) are full synthetic heavy duty extreme pressure multi-grade gear oils manufactured with quality synthetic base oil. CAM2® Magnum Full Synthetic Gear Oil LS are designed to meet the service demands of automobile, light truck and the latest heavy-duty manual transmissions, axles and drive units that call for API GI -5/MT-1.

| | 75W-90 | 75W-140 |
|-------------|---------------------|---------------------|
| 12/1 QUART | 12903- 51012 | 12903- 51112 |
| 3/1 GAL | 12903- 51031 | 12903- 51131 |
| 35 lb PAIL | 12903 -51005 | 12903- 51105 |
| 400 lb DRUM | 12903- 51055 | 12903- 51155 |



CAM2 ® Magnum® Full Synthetic Gear Oil 80W-140

GL-5

CAM2® MAGNUM FULL SYNTHETIC GEAR OIL 80W-140 is a full synthetic, heavy-duty gear oil formulated for heavy-duty differentials calling for GL-5 service. Applications include rear wheel bearings and universal joints, automobile, light and heavy-duty truck transfer cases, heavy construction and farm equipment. industrial gear units and manual transmissions.

| 35 lb | 12903- 50205 |
|--------|---------------------|
| 120 lb | 12903- 50216 |
| 400 lb | 12903- 50255 |

CAM2® Gear Oil

GL-1

CAM2® GL-1 GEAR OIL is a straight mineral gear oils intended for mild service in a broad range of automotive, manual transmission and industrial gear and bearing applications calling for API GL-1 performance, CAM2® SAE 90 GL-1 Gear Oil is used in gear sets operating under such mild conditions of low unit pressures and minimum sliding velocities, that untreated oil may be used satisfactorily. They may contain oxidation, rust and corrosion inhibitors, anti-foam agents and pour point depressants, GL-1 gear oils do not contain friction modifiers or extreme pressure additives



