



CAM2® ASHLESS HYDRAULIC OILS

CAM2® CAM2 ASHLESS PREMIUM HYDRAULIC OILS have an excellent antiwear performance and are designed for manufacturing and environmentally sensitive applications that require hydraulic oils containing no metals. CAM2® Ashless Premium Hydraulic Oils comply with most industrial applications and all grades are formulated according to the ISO viscosity grade classification.

	46	68
5 GAL	80565-12005	
55 GAL	80565-12055	80565-64755
TOTE	80565-12000	



For more information about pricing and additional product items, please contact your CAM2 Sales Representative.

Visit Our Website!
www.CAM2.com



Visit Our Facebook!
[@CAM2OIL](https://www.facebook.com/CAM2OIL)



Manufactured & Distributed by
CAM2® International, LLC
685 Haining Road,
Vicksburg, MS 39183 USA
Comments/Questions 800-338-2262

www.CAM2.com

CAM2
PREMIUM LUBRICANTS

TRACTOR
HYDRAULIC

(800) 338-CAM2
www.CAM2.com

MADE IN
U.S.A.

CAM2® PROMAX™ Premium Universal Tractor Hydraulic Fluid

CAM2® PROMAX™ TRACTOR HYDRAULIC FLUID J20-C is a true multi-service premium oil recommended for the hydraulic, wet brake, and transmission requirements of equipment manufacturers including John Deere®, Allis Chalmers®, J.I. Case®, Ford®, International Harvester®, Massey-Ferguson®, Allison®, AGCO® and White®.

It is recommended as a replacement fluid for the following manufacturer's specified products:

- Allis Chalmers® S25743, PF 821
- Allison® C-3, C-4
- Caterpillar® TO-2
- Denison® HF-0, HF-1, HF-2
- Detroit Diesel® Allison Division C-2, C-3, C-4 Fluid
- Deutz-Allis® HTF(PF821); 821XL
- Ford® New Holland M2C134 A/B/C/D; M2C86 B/C; M2C48 M2C53-A
- International Harvester® B-6 (Hy-Tran) MS-1209 (HY-TRAN ULTRA)
- J.I. Case® MS-1207 (Hy Tran Plus); MS-1204; MS-1205; MS-1206, MS-1210 (TCH) and B-6; TFD; Hi-Vis
- John Deere® J20A (Hy-Gard), J20C, J14B, J14C, J21A, 303, Quatrol®
- Kubota® UDT
- Massey-Ferguson® M1110; M1127 A/B; M1135; M1141 (Permatran III)
- Oliver® Type 55
- Renk® 874A/B (Doromat) Bus Transmissions
- Sauer-Sunstrand® HMS-103
- Stieger® HTF (SEM 17001)
- Versatile® HY-Gear (23, 24M)
- White® Q1766B, Q1826, Q1802, Q1705, Q1722
- Sperry-Vickers® I-286 S, M 2950 S

3/1 GAL	80565-16531
3/2 GAL	80565-16532
5 GAL	80565-16505
55 GAL	80565-16555
TOTE	80565-16500
BULK	80565-16511

CAM2® PROMAX™ Tractor Hydraulic Fluid J20-D

CAM2® PROMAX™ TRACTOR HYDRAULIC FLUID J20-D is a premium quality tractor hydraulic fluid blended from highly refined base stocks and formulated for long-term service under severe conditions. It is designed for use in equipment utilizing a common sump or requiring a single fluid for final drive, transmission, differential power take-off (PTO) units and wet brake systems. CAM2® PROMAX™ Tractor Hydraulic Fluid J20-D is a lower viscosity product blended to meet the viscosity limits of John Deere J20D specification.

5 GAL	80565-16605
55 GAL	80565-16655
BULK	80565-16611



CAM2® Agricultural Hydraulic Fluid

CAM2® AGRICULTURAL HYDRAULIC FLUID is a mono-grade (20W) fluid. It provides an economic solution to higher priced sump lubricants that protects hydraulics and final drives. It is environmentally friendly and is an excellent choice for general lubrication. CAM2® Agricultural Hydraulic Fluid is suitable for use in agricultural applications which call for an SAE 20W hydraulic oil.

5 GAL	80565-19905
55 GAL	80565-19955
BULK	80565-19911

CAM2® HYDRA-CAT 1000 Hydraulic Fluid

CAM2® HYDRA-CAT 1000 was specifically designed for hydraulic systems on off-road machinery, such as machine made by Caterpillar. CAM2® Hydra-cat 1000 provides excellent anti-wear protection and exceeds the required 900 PPM zinc

	SAE 10W	SAE 20W
55 GAL	80565-13155	80565-13255
BULK	80565-13111	80565-13211



CAM2® MPT Torque Fluid - T0-4

CAM2® MPT TORQUE FLUIDS are designed for use in heavy duty off road power shift transmissions. They have heavy duty friction modifiers to help clutches to lock up quickly and firmly. CAM2® MPT Torque Fluids have shown outstanding performance in all the manufacturers' friction tests. CAM2® MPT Torque Fluids are compatible with the various seal materials found in off road transmissions. They provide complete hydraulic system protection for the power shift and power steering mechanisms. MPT-10W is designed to give enhanced protection for light duty automatic transmissions.

	10W	30	50
5 GAL	80565-52505	80565-52605	80565-52705
55 GAL	80565-52555	80565-52655	80565-52755
TOTE	80565-52500	80565-52600	80565-52700
BULK	80565-52511	80565-52611	80565-52711



CAM2® All Season AW 5W-20 Hydraulic Oil

CAM2® ALL SEASON HYDRAULIC OIL is a high viscosity index hydraulic oil for use in mobile and industrial equipment operated in a wide range of sub-arctic and temperate climates. CAM2® ALL SEASON AW HYDRAULIC OIL's premium anti-wear hydraulic fluid formulation offers superior shear stability performance and outstanding low temperature characteristics. It is specially formulated for use in mobile equipment hydraulic circuits where wide temperature ranges are encountered. This product meets API viscosity 5W-20.

55 GAL	80565-14855
TOTE	80565-14800
BULK	80565-14811

