

CAM2 OIL TREATMENT

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: CAM2 Oil Treatment

SYNONYMS: Petroleum oil; Lube oil; Petroleum hydrocarbon; Lubricant

PRODUCT CODE: 814

PRODUCT USE: Engine Oil Treatment

MANUFACTURER'S NAME: CAM2 International, LLC

ADDRESS: P.O. Box 1119

Evergreen, CO 80437 Tel: 800-338-2262

EMERGENCY TELEPHONE NUMBER: UNITED STATES: 1 800 633 8253

These numbers are for emergency use only. INTERNATIONAL: 1 801 629 0667

If you desire non-emergency product information,

please call phone number listed below.

CUSTOMER SERVICE: 303-292-0595

MSDS FORM NUMBER: 814

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

APPEARANCE

Amber fluid, petroleum odor

CAUTION!

HEALTH HAZARDS

May be harmful if swallowed. May irritate eyes and skin.

POTENTIAL HEALTH EFFECTS

INHALATION This product is not likely to present an inhalation hazard at normal temperatures (**BREATHING**): and pressures. However, when aerosolizing, misting, or heating of this product,

high concentrations of generated vapor or mist may irritate the respiratory tract

(nose, throat, and lungs).

EYES: May cause irritation.

SKIN: May cause irritation. Not likely to be absorbed through the skin in harmful amounts.



CAM2 OIL TREATMENT

INGESTION May be harmful if swallowed. May cause throat irritation, nausea, vomiting, and **(SWALLOWING):** diarrhea. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

MEDICAL CONDITIONS AGGRAVETED BY EXPOSURE:

Individuals with pre-existing respiratory tract (nose, throat, and lungs) eye and/or skin disorders may have increased susceptibility to the effects of exposure.

CHRONIC:

EFFECTS:

Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis).

POTENTIAL ENVIRONMENTAL

No available information for this product.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Wt. Percent	Component	Synonym	CAS#
0 - 60	Severely hydrotreated heavy naphthenic petroleum oil	Petroleum distillates, Hydrotreated Heavy naphthenic	64742-52-5
0 - 60	Mineral Oil	Not Available	Mixture

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Oil mist, mineral (8012-95-1).

SECTION 4: FIRST AID MEASURES

INHALATION (BREATHING):

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if

breathing difficulty persists.

EYE: If irritation or redness from exposure to vapor develops, move away from

exposure into fresh air. Upon contact, immediately flush eyes with plenty of lukewarm water, holding eyelids apart, for 15 minutes. Get medical attention.

SKIN: Remove affected clothing and shoes. Wash skin thoroughly with soap and

water. Get medical attention if irritation or pain develops or persists. If product is injected under pressure into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, a physician

should immediately evaluate the individual as a medical emergency.

INGESTION: (SWALLOWING) Do NOT induce vomiting. Immediately get medical attention. If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give anything to an unconscious person by the mouth.



CAM2 OIL TREATMENT

NOTE TOTreat symptomatically and supportively. Treatment may vary with condition

PHYSICAINS: of victim and specifics of incident.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED): 275°F (135°C) (Pensky-Martens. Minimum)

FLAMMABLE LIMITS IN AIR: Lower: Not Available Upper: Not Available

AUTOIGNITION

PRODUCTS:

TEMPERATURE: Not available

HAZARDOUS COMBUSTION Decomposition and combustion materials may be toxic.

Burning may produce sulfur oxides, aldehydes, ketones, carbon monoxide and unidentified organic compounds.

CONDITIONS OF Sparks or flame. Products may burn, but does not ignite

FLAMMABILITY: readily.

EXTINGUISHING MEDIA: Carbon dioxide, regular foam, dry chemical, water spray, or

water fog. Water or foam may cause frothing.

HAZARD RATING NFPA 704 HAZARD IDENTIFICATION

0= LEAST HEALTH HAZARD (BLUE) 1
1= SLIGHT FIRE HAZARD (RED) 1
2= MODERATE REACTIVITY (YELLOW) 0

3= HIGH SPECIFIC HAZARD (WHITE)

4= EXTREME

FIRE FIGHTING INSTRUCTIONS: Keep storage containers cool with water spray. A positive-

pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

FIRE AND EXPLOSION

HAZARDS:

Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Products are not

sensitive to mechanical impact or static discharge.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **Section 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION**. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean spark-proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.



CAM2 OIL TREATMENT

SECTION 7: HANDLING AND STORAGE

HANDLING:

Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. This product has a low vapor pressure and is not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating this product, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing and shoes.

SHIPPING AND STORING:

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain residue and can be dangerous.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES Component Exposure Limits

Mineral Oil

ACGIH: 5mg/m³ TWA (sampled by method that does not collect vapor) (related to Oil mist, mineral)

10 mg/m³ STEL (sampled by method that does not collect vapor) (related to Oil mist, mineral)

OSHA Final: 5 mg/m³ TWA (related to Oil mist, mineral)

ENGINEERING CONTROLS:

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION:

No respiratory protection is normally required. Use NIOSH-certified P- or R-series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

EYE PROTECTION: Where eye contact is likely, wear safety glasses; contact lens use is not

recommended.



CAM2 OIL TREATMENT

SKIN Where skin contact is likely, wear neoprene, nitrile or equivalent protective

PROTECTION: gloves; use of natural rubber or equivalent gloves is not recommended. When

product is heated and skin contact is likely, wear heat-insulating gloves, boots,

and other protective clothing.

To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant face shield, boots, apron, coveralls, long

sleeve shirts, or other protective clothing.

PERSONAL Use good personal hygiene. Wash thoroughly with soap and water after

HYGIENE: handling product and before eating, drinking, or using tobacco products.

Clean affected clothing, shoes, and protective equipment before reuse.

Discard leather articles, such as shoes, saturated with these products.

OTHER

PROTECTIVE EQUIPMENT:

Where spills and splashes are likely, facilities storing or using these products should be equipped with emergency eyewash and shower,

both equipped with clean water, in the immediate work area.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE,

APPEARANCE Amber liquid

ODOR: Petroleum odor

ODOR THRESHOLD: Not available

MOLECULAR WEIGHT: Not applicable

SPECIFIC GRAVITY: 0.89 (Estimated) (water=1) (approximately)

VAPOR DENSITY: >1 (Air = 1)

VAPOR PRESSURE: less than 0.1 mm Hg at 68 € (20 °C)

RELATIVE DENSITY: 0.889 g/cm³ at 60°F (15.5°C)

INITIAL BOILING POINT: Not available

BOILING RANGE Not available

FREEZING/MELTING POINT: Not available

pH: Not applicable

EVAPORATION RATE: Not available

SOLUBILTY IN WATER: Insoluble

FLASH POINT: 275°F (135°C) (Pensky-Martens. Minimum)

FLAMMABILITY: Not available

FLAMMABLE LIMITS IN AIR: LOWER: Not available UPPER: Not available

AUTOIGNITION TEMPERATURE: Not available



CAM2 OIL TREATMENT

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal temperatures and pressures. Avoid sparks, or flame.

INCOMPATIBILITY: Avoid oxidizing agents.

REACTIVITY: Polymerization is not known to occur under normal temperatures and

pressures. Not reactive with water.

HAZARDOUS DECOMPOSITION

None under normal temperatures and pressures. Also see **Section 5**:

HAZARDOUS COMBUSTION PRODUCTS.

PRODUCTS:

SECTION 11: TOXICOLOGICAL INFORMATION

ROUTES OF EXPOSURE: Skin, Eyes, Ingestion, and Inhalation.

ACUTE EFFECTS: May be harmful if swallowed. May irritate eyes and skin. May cause

throat irritation, nausea, vomiting and diarrhea. Aspiration hazard: breathing product into the lungs during ingestion or vomiting may

cause lung injury and possible death.

REPEATED DOSE

EFFECTS:

Prolonged or repeated inhalation of oil mist may cause oil pneumonia, lung tissue inflammation, and/or fibrous tissue formation. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling

(dermatitis).

SENSITIZATION: Based on best current information, there is no known human

sensitization associated with this product.

MUTAGENICITY: Experimental evidence suggests that this product does not cause

mutagenesis.

CARCINOGENICITY Based on best current information, there is no known carcinogenicity as

regulated by OSHA; as categorized by ACGIH A1 or A2 substances; as categorized by IARC Group 1 Group 2A, or Group 2B agents as either known carcinogens or substances for which there is limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in

experimental animals.

REPRODUCTIVE

TOXICITY:

Based on best current information, there is no known reproductive

toxicity associated with this product.

TERATOGENICITY: Based on best current information, there is no known teratogenicity

associated with this product.



CAM2 OIL TREATMENT

NEUROTOXICITY: High vapor / aerosol concentrations (attainable only at elevated

temperatures) may cause central nervous system effects such as

dizziness, drowsiness or headaches.

TOXICITY DATA:

Component Analysis – LD50/LC50

Mineral Oil

Dermal LD50 Rabbit >5000 mg/kg Oral LD50 Rat >5000 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: No information available for this product.

PERSISTENCE/

Not readily biodegradable.

DEGRADABILITY:

BIOACCUMULATIVE No information available for the product.

POTENTIAL:

MOBILITY IN

Base oil component(s) – Low solubility and floats; expected to

ENVIRONMENTAL

MEDIA:

migrate from water to the land.

OTHER ADVERSE

EFFECTS:

Not available.

OCTANOL/WATER

PARTITION

Not available.

COEFFICIENT:

VOLATILE ORGANIC Negligible

COMPOUNDS:

AQUATIC RELEASE: Advise authorities if product has entered or may enter watercourses

or sewer drains.

SECTION 13: DISPOSAL CONSIDERATIONS

DISPOSAL: Dispose in accordance with federal, state, provincial, and local regulations.

Regulations may also apply to empty containers. The responsibility for proper

waste disposal lies with the owner of the waste.

USEPA WASTE

CODES:

This product, if discarded, is not expected to be a characteristic or listed

hazardous waste. If recycled in the USA, it must be managed in accordance with 40 CFR Part 279. Processing, use, or contamination by user may change

the waste code(s) applicable to the disposal of these products.



CAM2 OIL TREATMENT

SECTION 14: TRANSPORT INFORMATION

LAND (DOT): Not regulated as a hazardous material for Land Transport.

(Shipping Name)

LAND (TDG): Not regulated as a dangerous good for Land Transport.

(Shipping Name)

EMERGENCY RESPONSE Not applicable

GUIDE NUMBER: Reference North American Emergency Response Guidebook.

SECTION 15: REGULATORY INFORMATION

SARA SECTIONS Based on the ingredients listed in SECTION 3, this product does not

302, 304 contain any "extremely hazardous substances" listed pursuant to Title III of the

Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302

or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

SARA SECTIONS This product pos 311 AND 312 370 and is subjective Superfund Amen

This product poses the following health hazard(s) as defined in 40 CFR Part 370 and is subject to the requirements of sections 311 and 312 of Title III of

Superfund Amendments and Reauthorization Act of 1986 (SARA):

Immediate (Acute) Health Hazard No
Delayed (Chronic) Health Hazard No
Physical Fire No
Physical Sudden Release of Pressure No
Physical Reactive No

SARA SECTION This product does not contain chemicals subject to the supplier

notification requirements of the SARA 313 Toxic Release Program.

CERCLA Based on the ingredients listed in SECTION 3, this product does not contain

any "hazardous substances" listed pursuant to the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA)

in 40 CFR Part 302, Table 302.4.

CALIFORNIA: This product does not contain any chemicals which the State of California has

found to cause cancer, birth defects or other reproductive harm.

TSCA: All components listed in **SECTION 3** are listed on, or are exempted from the

requirements.

SECTION 16: OTHER INFORMATION

DATE ISSUED: April 8, 2010

©2010 CAM2 International, LLC

313



CAM2 OIL TREATMENT

SUPERSEDES: January 14, 2008

REVISION NO.

REVISION INFORMATION: MSDS update adding additional Globally Harmonized System (GHS)

requirements.

LABEL/OTHER INFORMATION: Not available.

MSDS FORM NUMBER: 814

The information in this Safety Sheet was obtained from sources which we believe are reliable. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT. This safety sheet was prepared and is to be used only for this product. If the product is used as a component in another product, this safety sheet information may not be applicable.

-END OF DOCUMENT-