



PRODUCT BULLETIN

PROMAX[®] DRIP OIL

PRODUCT #101

CAM2 PROMAX[®] DRIP OIL contains only premium quality paraffinic hydrotreated oil. CAM2 DRIP OIL is manufactured using state of the art distillation and hydrotreatment producing an extremely consistent high quality light colored paraffinic finished product.

CAM2 PROMAX[®] DRIP OIL exhibits great lubrication, oxidation and cold temperature characteristics making it an excellent choice to lubricate bearings found on vertical shaft driven deep well turbine pumps. It is a light straw color and recommended for use on vertical shaft driven deep well turbine pumps equipped with a drip oiler. CAM2 Promax[®] Drip Oil is highly refined base oil that contains no harmful additives that may contaminate underground water supplies. The naturally high viscosity index will provide consistent flow with temperature variations.

Note that some states or areas may require the use of food grade drip oil. CAM2 Promax[®] Drip Oil is not H-1 registered for incidental food contact.

TECHNICAL DATA

| PROPERTY | TYPICAL |
|-------------------------|---------|
| Specific Gravity @ 60°F | 0.8539 |
| Viscosity @ 40°C, cSt | 12.65 |
| Viscosity, 100°C, cSt | 3.0 |
| Viscosity Index | 91 |
| Pour Point: °C | -18 |
| Color | L0.5 |



CAM2 INTERNATIONAL, LLC

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 800-338-2262

www.CAM2.com