



## PRODUCT BULLETIN

# **CAM2 Blue Blood Elite HD Synthetic Engine Oil SAE 15W-40**

*API CK-4*

PRODUCT #392

**CAM2 BLUE BLOOD ELITE HD SYNTHETIC MOTOR OIL** with Engine DETOX, Fast Action Additives is the premium choice for preventative maintenance in vehicles that operate under severe driving and temperature conditions. CAM2 Blue Blood ELITE HD Synthetic Engine Oil 15W-40 provides superior wear protection, thermal and shear stability, and oxidative resistance. It meets or exceeds API service category CK-4, CI-4 Plus.

**CAM2 BLUE BLOOD ELITE HD SYNTHETIC ENGINE OIL 15W-40** is suitable for use in Detroit Diesel®, Cummins®, Mack®, Caterpillar® and Volvo®. It is suitable for most naturally aspirated or turbo-charged diesel engines as well as exhaust gas re-circulated engines used in truck or off-highway equipment.

## FEATURES

**CAM2 Blue Blood ELITE HD Synthetic Engine Oil 15W-40 provides:**

- Excellent protection from deposits at all operating temperatures.
- Excellent anti-wear, anti-foaming, anti-rust protection
- Excellent corrosion protection (EGR critical)
- Excellent soot control
- Extended drain capable

## APPLICATIONS

**CAM2 Blue Blood ELITE HD Synthetic Engine Oil 15W-40 may be recommended for the following uses:**

- When CK-4 CJ-4, CI-4 PLUS, CI-4, CH-4, oils are required
- When SN, SM, SL, SJ, SH, SG, SF oils are required
- All Heavy Duty Diesel Engines and EGR Designed Engines
- Cummins - CES 20086 (5W-40/10W-30) 20081(15W-40)
- Mack - EOS-4.5, EO-O, Premium Plus 07
- MB 228.31
- Renault - RLD-4, RLD-3
- Caterpillar - ECF-3
- Detroit Diesel - DFS93K222, DFS93K218



Applications continued on pg 2.

**CAM2 INTERNATIONAL, LLC**

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 800-338-2262  
www.CAM2.com



## PRODUCT BULLETIN

# **CAM2 Blue Blood Elite HD Synthetic Engine Oil SAE 15W-40**

*API CK-4*

PRODUCT #392

### **APPLICATIONS (continued)**

- Ford WSS-M2C171-F1
- MAN - M3575, M3275
- Volvo - VDS 4.5
- MTU 2.1
- JASO DHD-1
- JD Tier IV LDF-4
- MIL PRF-2104

### **TYPICAL PROPERTIES**

SAE GRADE	15W-40
Product Code	392
API	CK-4, CJ-4, CI-4 Plus
API Gravity	28.6
Viscosity @ 100°C, cSt	15.5
Sulfated Ash, wt.%	1
Total Base Number	7.5
CCS Viscosity (mPa.s)	<7000@-20
Pour Point:°C	-37
Flash Point:°C	238

Always consult owners manual for proper viscosity and performance recommendations

**Contact your CAM2 representative or CAM2 distributor for additional information.**

**CAM2 INTERNATIONAL, LLC**

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 800-338-2262  
www.CAM2.com