



PRODUCT BULLETIN

ATF 4

Synthetic Automatic Transmission Fluid

PRODUCT #328

CAM2 ATF 4 Fluid is a full synthetic automatic transmission fluid formulated by CAM2 for use in Chrysler Corporation automatic transmissions and transaxles. This is compatible with all transmissions that require Mopar ATF+®, Mopar ATF+2® and Mopar ATF+3®. CAM2 ATF 4 Fluid is recommended by CAM2 for use in all applications specifying Mopar ATF+4® or Type MS-9602 fluid.

Not recommended for automatic transmission/transaxles where DEXRON® VI transmission fluid is specified.

FEATURES

CAM2 ATF 4 Fluid's Advantages:

- Thermal Stability
- Positive Shifting
- Anti Foaming
- Anti-wear & Rust Protection
- All Temperature Protection

APPLICATIONS

CAM2 ATF 4 Fluid may be recommended for the following:

- Mopar ATF+™
- Mopar ATF+2™
- Mopar ATF+3™
- Mopar ATF+4™
- Type MS-9602 fluid
- Type MS-7176 fluid

See Technical Data on pg 2.



CAM2 INTERNATIONAL, LLC

685 Haining Road, Vicksburg, MS 39183

(833) 715-0016 • www.CAM2.com



PRODUCT BULLETIN

ATF 4

Synthetic Automatic Transmission Fluid

PRODUCT #328

TECHNICAL DATA

Product Code	328
Gravity, API, ASTM D 287	32
Flash Point, COC, °F (°C) ASTM D 92	365 (185)
Fire Point, COC, °F (°C) ASTM D 92	428 (220)
Viscosity cSt, ASTM D 445, at 40°C	30.4-37.5
Viscosity cSt, at 100°C	7.0
Viscosity cP, at -40°C, ASTM D2983	15,000
Viscosity Index, ASTM D 2270	175
Pour Point, °F (°C) ASTM D 97	-54 (-48)
Color	Red

Contact your CAM2 representative or CAM2 distributor for additional information.

CAM2 INTERNATIONAL, LLC
685 Haining Road, Vicksburg, MS 39183
(833) 715-0016 • www.CAM2.com