



PRODUCT BULLETIN

Full Strength Antifreeze & Coolant

PRODUCT #801

CAM2 Full Strength Antifreeze & Coolant is a low silicate formulation that provides outstanding corrosion protection. In addition, **CAM2 Full Strength Antifreeze & Coolant** contains an advanced additive inhibitor system to provide broader range protection than most coolants. This includes ingredients to disperse minor oil leakage, suppress foaming, prevent fouling and control hot surface scaling. Premium conventional antifreeze formulation contains sufficient nitrite levels so that it can be used in both passenger car and trucking fleets without the need for any additional pre-charge.

FEATURES

This antifreeze meets ASTM D-3306

FEATURES

- Automotive-Passenger Car & Light Truck
- Natural Gas Compressor Engines
- Air Compressor Engines
- Drilling Equipment
- Stationary Engines
- Irrigation Equipment
- Heat Tracing Systems

All CAM2 Antifreeze products are formulated with bitterant agents to ensure protection against ingestions by humans, pets and wildlife.

TECHNICAL DATA

Product Code	801
Specific Gravity @ 60°F:	1.090-1.125
Freeze Point (°F):	-5
pH (Concentrate):	8.0-10.5
Chloride (ppm):	<25
Color	Green

Note: The values shown are representative of current production and may vary within modest ranges.



CAM2 INTERNATIONAL, LLC
685 Haining Road • Vicksburg, MS 39183
(Toll Free) 833.715.0016 • www.CAM2.com