



PRODUCT BULLETIN

Global Prediluted 50/50 Antifreeze

PRODUCT #832

CAM2 Global Prediluted 50/50 Antifreeze possesses a proprietary combination of complex carboxylic acid derivatives to protect all six standard metal alloys (iron, copper, brass, solder, aluminum, and steel) found in radiator systems. Its hybrid organic acid technology (HOAT) additive package is formulated with a stabilization system to improve the durability of its carboxylate salt base and extend its range of compatibility with both conventional inorganic salts and OAT-type antifreezes. It contains no borates, phosphates, nitrates or silicates. In addition, the product will not cause turbidity, precipitation, or inhibitor effectiveness reduction when mixed with carboxylate based coolants such as Dex-Cool®* or Texaco®* Extended Life nor with conventional coolants such as Prestone®, Zerex®, or Peak®*. In automobiles, this antifreeze should provide service life in excess of 5 years or 150,000 miles. It is ideal for initial fills, coolant change-outs or top-offs.

FEATURES

This antifreeze meets ASTM D-3306

FEATURES

- Automotive-Passenger Car & Light Truck
- Natural Gas Compressor Engines
- Air Compressor Engines
- Stationary Engines
- Irrigation Equipment
- Heat Tracing Systems
- Line Heaters

All CAM2 Antifreeze products are formulated with bitterant agents to ensure protection against ingestions by humans, pets and wildlife. All CAM2 Antifreeze Premix 50/50 products are manufactured using only deionized water.

TECHNICAL DATA

Product Code	832
Specific Gravity @ 60°F:	1.055-1.085
Freeze Point (°F):	-34
Reserve Alkalinity (ml):	3 mL (concentrate)
pH (Concentrate):	8.0-10.0
Chloride (ppm):	<25
Color	Chameleon

Note: The values shown are representative of current production and may vary within modest ranges.

