



PRODUCT BULLETIN

DEXRON®-VI Multi-Vehicle Full Synthetic ATF

PRODUCT #298

CAM2 DEXRON®-VI Multi-Vehicle Full Synthetic Automatic Transmission Fluid is a universal ATF specifically designed for use in modern automatic transmissions. CAM2 DEXRON®-VI Multi-Vehicle Full Synthetic ATF is a licensed DEXRON®-VI ATF and is the most recommended GM* approved specification for vehicle of model years 2006 and newer. CAM2 DEXRON®-VI Multi-Vehicle Full Synthetic ATF provides additional oxidation control required for extended drain intervals, excellent low temperature performance for fuel economy, and superb shear stability.

CAM2 DEXRON®-VI Multi-Vehicl Full Synthetic ATF is recommended for use in: GM DEXRON®-VI, DEXRON® III/III(H)/IIE, DEXRON® II, Ford MERCON® LV, Hyundai/Kia SP- II/III/IV, Toyota WS,T-III, T-IV Mercedes Benz®, Honda® Z-1, Allison®, and Nissan® Matic Fluids. Cannot be used in extended drain heavy duty diesel, Type F, CVT or DCT applications. Refer to owner’s manual for manufacturer’s recommendation.

Full synthetic formula provides optimum low temperature performance – PAO base stock provides excellent cold weather performance ensuring smooth shifts throughout the power band

Wide application range – Exceeds requirements of a wide range of OEM specifications for reduced inventory

Unsurpassed fuel economy - Low viscosity formula for maximum fuel efficiency in modern automatic transmissions

Eliminates shudder – Patented additive technology eliminates shudder for smooth, consistent shifts

GM DEXRON®-VI
Approved License Number: J-60177

FEATURES

- **Lower Foaming** - Good demulsability and oxidative stability to suppress foaming
- **Excellent Oxidation Stability** - Provides outstanding resistance against sludge and deposit formation and excellent high temperature performance
- **Better Protection against Pitting** – Excellent anti-friction performance eliminates pitting and wear to critical components
- **Highly Shear Stable** - Highly shear stable viscosity modifiers improve viscosity retention to ensure maximum protection in all operating environments

TECHNICAL DATA

Product Code	298
Kinematic Viscosity, D-445 cSt@100°C	5.91
Kinematic Viscosity, D-445 cSt@40°C	29.11
Viscosity Index, Calculated, D2270	153
Brookfield Viscosity, D-2893 cPat @ -40°C	10,000
Color	Red

See Applications on pg 2.



PRODUCT BULLETIN

DEXRON®-VI Multi-Vehicle Full Synthetic ATF

PRODUCT #298

APPLICATIONS

CAM2 DEXRON®-VI Multi-Vehicle Full Synthetic ATF fully licensed and approved by General Motors under registration # J-60153 for use in GM transmissions for model year 2006 and newer calling for Dexron® VI

Recommended where Ford Mercon® LV is recommended

Suitable for use in passenger car automatic transmission applications calling for use of a low viscosity ATF.

Not for use in CVT (Continuously Variable Transmissions) or DCT (Dual Clutch Transmissions) which require specialized fluids. Also not recommended for applications calling for Ford Mercon® SP.

Contact your CAM2 representative or CAM2 distributor for additional information.

Low Viscosity Specifications

Aisin Warner JWS 3324 (WS)	JASO M315-2013 1A-LV
Aisin Warner AW-1	Land Rover LR023288
Audi/VW G 060 162 (ZF Lifeguard fluid 8) (ZF No. S671 090 312)	Mazda ATF FZ
Audi/VW G 055 540 (A2)	Mitsubishi Diaqueen SP-III
Chrysler/Dodge/Jeep 68043742AA	Mitsubishi Diaqueen SP-IV
Chrysler/Dodge/Jeep 68333587AA	Mitsubishi Diaqueen AW
Ford MERCON® LV (FF-WSS-M2C-938A/SF, XT-10 QLV)	Mitsubishi Diaqueen J3
GM DEXRON®-VI (LICENSED)	Mitsubishi Diaqueen ATF PA
GM/GMC/Opel/Saturn 88863400	NAG 1 (Chrysler, Jeep, Cherokee)
GM/GMC/Opel/Saturn 88863401	Nissan Matic Fluid S
Honda ATF Ultra II	Opel/GM 9986195
Honda DW-1	Shell M-1375.4
Honda Type 3.0	Suzuki ATF AW-1
Honda Type 3.1	Toyota ATF WS JWS 3324
Hyundai/Kia SP-IV (00232-1904/04500-00115)	Volvo PN 31256774/31256675
Hyundai/Kia SP-IV M (SP4-M)	VW G055 540 (A2)
Hyundai/Kia SP-IV-RR	VW G 055 162-A2, -A6 (ZF Lifeguard fluid 6 Plus)
Hyundai/Kia NWS 9638	VW G 060 162 (ZF Lifeguard fluid 8)
ISUZU SCS Fluid	VW G US 000 162
Jaguar Fluid 8432	ZF 8 speed transmissions 68218925AA
Jaguar 02JDE26444	ZF 9 speed transmissions

Applications Continued on next page

High Viscosity Specifications

(CAM2 Dexron VI has displayed suitable performance in the following applications. Dexron VI is a low viscosity specification, as a result this product may not meet all viscometric parameters of the below specifications.)

High Viscosity Specifications			
Acura ATF-Z1	Ford/Lincoln/Mercury XT-2-QSM	KIA ATF SP-II, SP-III, SP-IV, P-IVM,	Shell 3403, M115, LA 2634
Aisin Warner JWS 3309 (T-IV) &	Ford ESP-M2C166H, XL-12	Lexus JWS 3309	Shell L 12108
Allison C-3 & C-4	Fuso ATF-II	MAN 339A	Ssang yong DSIH 5M-66
	Fuso ATF-SPIII	Mazda ATF D-II	Subaru ATF
ATF RED 1, RED 1K	Fuso ATF-A4	Mazda ATF M-III	Subaru K0140Y0700
Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)	GM9986195 (Aisin AW, JWS 3309)		Subaru ATF 5AT
Audi/VW G 052 025-A2	GM TASA	Mazda ATF F-1	Subaru DEXRON®-II
Audi/VW G 053 025-A2	GM DEXRON®-II	Mazda ATF S-1	Subaru ATF, ATF HP
Audi/VW G 052 162-A1/A2	GM DEXRON®-IID	Mazda ATF N-1	Suzuki AT OIL 5D06
Audi/VW G 055 025 A2 (JWS 3309)	GM DEXRON®-IIE	MAZDA ATF 3317	Suzuki ATF 2326
Audi/VW G 055 529 A2	GM DEXRON®-IIIG	MINI COOPER T-IV	Suzuki ATF 2384K
Audi/VW G 052 162 (ZF Lifeguard fluid 5) (ZF No. S671 090 170)	GM DEXRON®-IIIH	Mitsubishi Diaqueen SK	Suzuki JWS 3309
Audi/VW G 055 162-A2, -A6 (ZF Lifeguard fluid 6 Plus) (ZF No. S671 090 281)	GM 1940700	Mitsubishi Diaqueen SP-II	Suzuki ATF 3314
Audi/VW G 052 990	GM 1940767	Mitsubishi Diaqueen J2	Suzuki ATF 3317
Audi/VW 052 055	GM 21005966	Nissan Matic Fluid C	Texaco 7045-E
Bentley PY112995PA	GM 22717466	Nissan Matic Fluid D	Texaco 8072B
BMW JWS 3309 (T-IV)	GM 88900925	Nissan Matic Fluid J	Texaco N402
BMW LA2634	GM 9986195	Nissan Matic Fluid K	Toyota ATF D-II
BMW LT71141 (ZF 5 HP 18FL/19FL/24A)	GM 93160393	Opel/GM 19 40 700	Toyota ATF D-III
BMW ZF 5HP18FL, 5HP24, 5HP30	GM/GMC/Opel/Saturn AW1	Opel/GM 19 40 767	Toyota ATF T-III
BMW 7045E	GM/GMC/Opel/Saturn V1	Opel/GM 21005966 Transaxle	Toyota ATF T-IV
BMW ETL 8072B	Hino Blue ribbon ATF	Opel/GM 22 17466	Vickers M2950-S, I-286-S
BMW MINI	Honda ATF-Z1 (except in CVTs)	Opel/GM 88900925	Voith 55.6335.xx (G607)
BMW 8322152426	Hyundai/Kia SP-III, Red 1	Peugeot ZF 4HP20	Voith Svc Bltn #013 and #118
BMW ATF6 83222355599	Hyundai/Kia Dex-II/ SP-II	Peugeot/ Citroen Z 000169756	Volvo 97325
Bosch TE-ML 09	Hyundai/Kia JWS 3314	Peugeot/ Citroen (PSA) AL4 Automatic gearbox oil (#9730.AE)	Volvo 97335
CAT TO-2	Hyundai/Kia 040000C90SG	Porsche ZF 5HP19FL, ZF 5HP20, LT71141	Volvo CE 97340
Chrysler/Dodge MOPAR AS 68 RC and AS 69 RC (T-IV), JWS	Hyundai/Kia NUMM040 CH20	Porsche ATF 3403-M115,	Volvo PN 1161521
Chrysler/Dodge/Jeep 05127382AA	Idemitsu K17 3100 PL085	Porsche T-IV (JWS 3309)	Volvo PN 1161540/1161640
Chrysler/Dodge/Jeep 68171866AA	ISUZU BESCO ATF-II	Porsche 000 043 205 09	Volvo PN 1161621
Chrysler ATF+, +2, +3 (MS 7176E), +4 (MS9602)	ISUZU BESCO ATF-III	Porsche 999 917 547 00 (A2)	VW 5 HP (ZF 5 HP 30)
Daewoo LT 71141	ISUZU BESCO ATF SP	Porsche 000 043 205 28	VW 5HP (18FL, 30)
Daihatsu AMMIX ATF D-II	ISUZU 08200-9001	Porsche Z 000169756	VW 5HP (19FL, 24A)
Daihatsu AMMIX ATF D-III SP	Jaguar ATF 3403 M115, ATF 3403-M115,	Renault DPO/AL4	VW G-055-025 A2 (JWS 3309)
Esso LT 71141	Jaguar ATF LT71141,ZF5HP24	Renault Matic D2	VW G 052 162 (ZF Lifeguard fluid 5)
FIAT T-IV type, JWS 3309	Jaguar JLM20238	Renault Samsung SATF-D	VW TL 521 62
Ford MERCON®	Jaguar ATF 3403 JLM20238,	Saab T-IV (JWS 3309)	ZF all 3 & 4 speed transmission
Ford FNR5 (Mazda M5, XT-9-QMM5)	Jaguar K17	Saab 93 165 147	ZF TE-ML 05L
Ford WSS M2C 138CJ, 166H	Jaguar JLM 20292	Saab 93 160 393	ZF TE-ML 09
Ford WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309	JASO M315-2013 1A	Saturn T-IV (JWS 3309)	ZF TE-ML 11A, 11B, 21L
Ford/Lincoln/Mercury XT-2-QDX (M)	JASO M315-2013 2A	Scion (all vehicles)	