

PRODUCT BULLETIN

PROMAX™ Tractor Hydraulic Fluid J20-D

PRODUCT #166

CAM2 PROMAX™ J20D Tractor Hydraulic Fluid is a premium quality low temperature tractor hydraulic fluid blended from highly refined base stocks and formulated for long-term service under severe conditions. It is designed for use in equipment utilizing a common pump or requiring a single fluid for final drive, transmission, differential power take-off (PTO) units and wet brake systems.

CAM2 PROMAX™ J20D Tractor Hydraulic Fluid is a low viscosity formulation designed for use in colder applications where it is desired that the product maintains its excellent lubrication in colder temperature applications.

CAM2 PROMAX™ J20D Tractor Hydraulic Fluid has been specifically formulated to meet the applications listed below resulting in one fluid for many transmission/torque converter and hydraulic fluid requirements.

Equipment manufacturer recommendations and conventional guides to lubricant selection should be followed to determine the suitability of **CAM2 PROMAX™ J20D Tractor Hydraulic Fluid** for a specific application.

FEAUTRES

- Excellent extreme Pressure (EP) properties
- Excellent oxidation resistance and corrosion protection
- Excellent anti-foam properties
- Excellent anti-rust properties
- Excellent anti-wear properties
- Excellent low temperature performance characteristics
- Helps maintain seals and gaskets used in modern tractors

TECHNICAL DATA

Product Code	5W-20
SAE Grade	195/383
Flash Point °C/ °F	-51/-60
Color	4.0 max
Viscosity cSt @ 40°C	34
Viscosity cSt @ 100°C	7.5
Viscosity Index	180
Brookfield @ -40°C	20,000
Foaming - Sequence 1	0/0
- Sequence 2	10/0
- Sequence 3	0/0



CAM2 INTERNATIONAL, LLC

685 Haining Road, Vicksburg, MS 39183 USA • Tel: 800-338-2262
www.CAM2.com

See Applications on pg 2.

