

PRODUCT BULLETIN SuperLife Fleet HD Prediluted 50/50 Antifreeze

Extended Life Heavy Duty Antifreeze/Coolant (ELC)

PRODUCT #805

CAM2 SuperLife Fleet HD Truck Prediluted 50/50 Antifreeze is a versatile, high performance, pre-diluted automotive cooling system product designed for Heavy-Duty Truck application. **CAM2 SuperLife Fleet HD Truck Prediluted 50/50 Antifreeze** is formulated with premium glycol and a superior organic acid technology additive package. It is a silicate-, borate-, phosphate-free formulation for long lasting inhibition and corrosion protection. Protects aluminum and all other engine metals and provides long term, broad-range metal protection, minimizes hot surface scaling, and prevents heat transfer surface fouling due to minor oil leakage.

This antifreeze meets ASTM D-3306, ASTM D-4985, ASTM D-6210

APPLICATIONS

- Automotive-Passenger Car & Light Truck
- Stationary Engines
- Irrigation Equipment
- Natural Gas Compressor Engines
- Air Compressor Engines
- Heat Tracing Systems
- Line Heaters

All CAM2 Antifreeze products are formulated with bitterant agents to ensure protection against ingestions by humans, pets and wildlife. All CAM2 Antifreeze Premix 50/50 products are manufactured using only deionized water.

TECHNICAL DATA

Product Code	805
Specific Gravity @ 60°F:	1.055-1.085
Freeze Point (°F):	-34
Chloride (ppm)	<25
pH:	8.0-10.0
Nitrite (ppm):	2400-3200
Color	Red
Reserve Alkalinity (mL)	3.0 mL min.

Dilution with conventional coolants will reduce extended life benefits.

Always consult owner's manual to determine the specific maintenance, change over intervals, and Extender/SCA treat rate for your vehicle.

CAM2 INTERNATIONAL, LLC 211 Violet Street Suite 100 • Golden, CO 80401 Telephone 800/338-2262 • Fax: 303/679-8988 www.CAM2.com

