



PRODUCT BULLETIN

SuperLife Pre-Diluted Antifreeze

Extended Life Heavy Duty Antifreeze/Coolant (ELC)

PRODUCT #825

CAM2 SuperLife 50/50 Antifreeze possesses a proprietary combination of complex carboxylic acid derivatives to protect all six standard metal alloys (iron, copper, brass, solder, aluminum, and steel) found in radiator systems. Its hybrid organic acid technology (HOAT) additive package is formulated with a stabilization system to improve the durability of its carboxylate salt base and extend its range of compatibility with both conventional inorganic salts and OAT-type antifreezes. It contains no phosphates, nitrates, or silicates. In addition, the product will not cause turbidity, precipitation, or inhibitor effectiveness reduction when mixed with carboxylate based coolants nor with conventional coolants. In automobiles, this antifreeze should provide service life in excess of 5 years or 150,000 miles. It is ideal for initial fills, coolant change-outs or top-offs.

This antifreeze meets ASTM D-3306

APPLICATIONS

- Automotive-Passenger Car & Light Truck
- Natural Gas Compressor Engines
- Air Compressor Engines
- Drilling Equipment
- Stationary Engines
- Irrigation Equipment
- Heat Tracing Systems
- Line Heaters

All CAM2 Antifreeze products are formulated with bitterant agents to ensure protection against ingestions by humans, pets and wildlife.

TECHNICAL DATA

Product Code	825
Specific Gravity @ 60°F:	1.050-1.085
Freeze Point (°F):	-34
Reserve Alkalinity (ml):	10 ml. min.
pH (Concentrate):	10-11
Chloride (ppm):	<25
Color	Orange



CAM2 INTERNATIONAL, LLC

211 Violet Street Suite 100 • Golden, CO 80401
Telephone 800/338-2262 • Fax: 303/679-8988
www.CAM2.com